

500 LITERS

AMERICAN OAK BARREL



| | |
|----------------------|---------------------|
| Capacity (L.) | 500 |
| Stave thickness (mm) | 27 |
| Galvanised hoops | 8 |
| Chestnut wood hoops | no |
| Weight (kg) | 69 |
| Height (cm) | 112 |
| Ø chime (cm) | 77 |
| Ø bilge (cm) | 93 |
| Interior surface | 3,37 m ² |
| Riveted hoops | no |

TYPE OF OAK

American oak - Quercus Alba

Naturally seasoned in the open air 20 to 24 months minimum

Checked for the absence of contaminants, tests carried out by the EXACT laboratory, accredited by COFRAC under N°1-2201 (scope available on www.cofrac.fr)

CERTIFICATIONS / ACCREDITATIONS

Bureau Veritas issues a certificate for HACCP mastery of products manufactured by Tonnellerie Berthomieu - Certificate of conformity N° BV/177/RE

PACKAGING

Identification by single number

Transport Wrapping - Cardboard end protections / bubble paper / cling wrap

MANUFACTURE

| | |
|--------------------------------|--|
| Steaming | Barrels are steam treated |
| Traditional wood fire toasting | Light Toast (LT), Medium Toast (MT), Medium Toast + (MT+), Heavy Toast (HT) |
| Bung hole | Cauterized - Diameter 48/52 |
| Heads | Oak tongued and grooved up to 300 litres Oak with stainless steel pins and natural fixations above 300 litres |
| Testing for Water Tightness | High pressure hot water |
| Options | Toasted Heads Hoops painted black Special laser engraving Spigot hole Wooden or silicone bung |